Compact Naboo





Compact combi ovens for small and medium catering businesses and home use. *

An elegant and compact design, ideal for kitchens which don't have a lot of space and are "on view". Available in 4 models with different sizes and tray capacities. Simple, intuitive commands with a 7-inch, LCD, HD capacitive touch screen display.







061



101



061



Naboo@home

You can now have a professional oven in your kitchen at home as well. Easy and convenient to install because it has been specially designed to fit into standard 60 cm household kitchen modules.

With the WIFI connection, you can also access the Nabook.cloud website and get inspiration from the hundreds of international recipes available.

Ideal voltages and power supplies for household installations

| Models | Power | GN chamber capacity 2/3 GN (352x325 mm) | Pitch (mm) | Electrical Power (kW) | Power supply voltage * (V) | |
|----------|------------|--|---------------|-----------------------------|----------------------------------|--|
| COEN026R | (5) | 6x2/3 | 60 | 2,75 | 1N AC 230V - 50 Hz | |
| COEN026R | (4) | 6x2/3 | 60 | 3,70 | 1N AC 230V - 50 Hz | |

Direct steam model - Standard configuration

| Models | Power | GN chamber capacity 2/3 GN (352x325 mm) 1/1 GN (530x325 mm) | Pitch (mm) | Number of meals | Electrical power (kW) | Nominal Gas thermal power (kW/kcal) | Absorption (A) | External dimensions (W x D x H mm) | Power supply voltage * |
|----------|-------------|---|---------------|--------------------|-----------------------------|---|----------------|---------------------------------------|------------------------|
| COEN026R | (4) | 6x2/3 | 60 | 20/50 | 5,25 | -/- | 8 | 510 x 625 x 880 | 3N AC 400V - 50 Hz |
| COENO61R | (5) | 6x1/1 | 60 | 30/80 | 7,75 | -/- | 11 | 510 x 800 x 880 | 3N AC 400V - 50 Hz |
| COEN101R | (5) | 10x1/1 | 60 | 80/150 | 15,5 | -/- | 22 | 510 x 800 x 1120 | 3N AC 400V - 50 Hz |
| CVEN061R | (5) | 6x1/1 | 60 | 30/80 | 8.25 | -/- | 12 | 875 x 650 x 705 | 3N AC 400V - 50 Hz |
| CAEMOOTK | 7) | 9X1/1 | 60 | 30/60 | 6,25 | -/- | 12 | 6/3 X 030 X /03 | 3N AC 400V - 50 HZ |
| CVGN061R | 4 | 6x1/1 | 60 | 30/80 | 0,5 | 8,5/7.310 | 2,2 | 875 x 650 x 705 | AC 230V - 50 Hz |

Steam generator model - Standard configuration

| CBEN061R | (4) | 6x1/1 | 60 | 30/80 | 8,25 | -/- | 12 | 875 x 650 x 705 | 3N AC 400V - 50 Hz |
|----------|------------|-------|----|-------|------|-----|----|-----------------|--------------------|

^{*} special voltages and frequencies upon request

